

	EOT057 ALPHA PRO 2400 LX 	EOT058 GAMMA PRO 2100 LX 	EOT059 POLAR PRO 3100 LX 	EOT060 SCORPIUS PRO 1750 LX 	EOT062 ANDROMEDA PRO 2000 LX 	EOT063 PHOENIX PRO 3800 LX 	EOT064 PEGASUS PRO 7000 LX 	EOT065 HERCULES PRO 8300 LX 	EOT066 CENTAURUS PRO 3500 LX 
DIODE	3W LED	CREE T6	CREE XTE-S2	CREE T6	CREE T6	CREE T6	5W LED	CREE XTE-S2	2 X CREE T6
LIGHTING INTENSITY [lx]:									
• MAX MODE	2400	2100	3100	1750	2000	3800	7000	8300	3500
• SUPER ECONO MODE	1200	500	550	350	600	700	3400	1350	900
VISIBILITY RANGE [m] ¹	200	200	200	200	200	200	200	200	200
VISIBILITY RANGE [m] ²	2000	2000	2000	2000	2000	2000	2000	2000	2000
NUMBER OF LIGHTING MODES	3	5	8	5	7	5	3	8	4
LIGHT MODES:									
• CONTINUOUS SUPER ECONO (25%)	✗	✓	✓	✓	✓	✓	✗	✓	✓
• CONTINUOUS ECONO (50%)	✓	✓	✓	✓	✓	✓	✓	✓	✓
• CONTINUOUS MAX (100%)	✓	✓	✓	✓	✓	✓	✓	✓	✓
• FLASHING MAX	✓	✓	✓	✓	✗	✓	✓	✓	✓
• SOS MAX	✗	✓	✓	✓	✓	✓	✗	✓	✗
• FLASHING FAST (MAX ~ SUPER ECONO)	✗	✗	✓	✗	✓	✗	✗	✓	✗
• SLOW FLASHING (MAX ~ SUPER ECONO)	✗	✗	✓	✗	✓	✗	✗	✓	✗
• TOUCH DIMMING	✗	✗	✗	✗	✓	✗	✗	✗	✗
TIME MAX. LIGHTING MODES [min.]:									
• CONTINUOUS SUPER ECONO (25%)	n/d	330	800	2000	6000	1800	360	2160	2400
• CONTINUOUS ECONO (50%)	200	300	560	470	950	200	n/d	560	1800
• CONTINUOUS MAX (100%)	70	50	100	400	400	170	150	100	400
• FLASHING MAX	140	205	200	720	n/d	160	325	2160	400
• SOS MAX	n/d	360	n/d	690	400	300	n/d	n/d	n/d
• FLASHING FAST (MAX ~ SUPER ECONO)	n/d	n/d	920	n/d	800 ~ 200	n/d	n/d	n/d	n/d
• SLOW FLASHING (MAX ~ SUPER ECONO)	n/d	n/d	2160	n/d	800 ~ 200	n/d	n/d	1850	n/d
BATTERY CHARGE INDICATOR	✗	✓	✓	✓	✓	✓	✗	✓	✓
BATTERY CAPACITY [mAh]	n/d	2200	1400	2200	2200	2200	2400	4000	4400
BATTERY CHARGING TIME / 2 A [min.]	n/d	75	115	145	280	145	145	250	240
CHARGING PORT	3 X AAA	MICRO USB	MICRO USB	MICRO USB	MICRO USB	MICRO USB	MINI USB	MICRO USB	MICRO USB
MOUNTING METHOD	HOLDER WITH RING	HOLDER WITH RING	HOLDER WITH RING	MOUNTING BRACKET WITH BLOCADE	MOUNTING BRACKET WITH BLOCADE	MOUNTING BRACKET WITH BLOCADE	HOLDER WITH RING	MOUNTING BRACKET WITH BLOCADE	MOUNTING BRACKET WITH BLOCADE
LAMP WEIGHT [g]:									
• WITHOUT MOUNTING	117	96	81	95	105	133	125	184	248
• WITH MOUNTING	140	106	102	125	144	163	148	210	278
HOUSING MATERIAL	ALUMINUM	ALUMINUM	ALUMINUM + ABS	ABS	ABS	ALUMINUM + ABS	ALUMINUM	ALUMINUM	ALUMINUM
DIMENSIONS [cm]	10.4 x 3.4 x 3.4	8.5 x 3.0 x 2.8	9.1 x 3.0 x 3.6	10.5 x 3.5 x 3.5	13.0 x 3.5 x 3.8	10.5 x 3.5 x 3.2	11.6 x 3.6 x 2.7	9.6 x 4.1 x 2.6	10.5 x 5.2 x 2.5
WATERPROOF CLASS	IPX 4	IP65	IPX 4	IPX 6	IPX 4	IPX 6	IPX 4	IPX 4	IPX 6
SET CONTENTS	lamp holder with ring	lamp micro USB wire holder with ring	lamp micro USB wire holder with ring	lamp micro USD wire mounting bracket with blocade	lamp micro USD wire mounting bracket with blocade	lamp micro USD wire mounting bracket with blocade	lamp mini USB wire holder with ring	lamp micro USD wire mounting bracket with blocade	lamp micro USD wire mounting bracket with blocade

¹ length of the road lit by the lamp, visible to the user of the lamp

² distance on the road from which the user of the lamp will be seen from an oncoming vehicle